

# 3100-4200 PSI PROFESSIONAL Power Washers

**GENERAC**<sup>®</sup>



Tough Cleaning Performance for Any Jobsite

# PROFESSIONAL POWER WASHERS

3100 – 4200 PSI

## DIRECT DRIVE

Tackle every tough cleaning job at work or on the farm. Generac's rugged power washers combine professional-grade features and user-friendly design. They're a breeze to set up, easy to maneuver and won't let you down.



**QUICK-CHANGE NOZZLE TIPS**  
Five included, for tackling any job

**DURABLE WELDED ROLL-CAGE STYLE FRAME**  
Protects the engine and pump

**STEEL-REINFORCED HOSE**  
Quick-change connectors make hose connections a snap

**PROFESSIONAL-GRADE ERGONOMIC SPRAY GUN**  
Cushion grip handle and easy-to-pull trigger reduce fatigue and improve comfort

**PRESSURE CONTROL VALVE**  
Provides complete control of water pressure for all applications

**POWERFUL GENERAC OHV HORIZONTAL-SHAFT ENGINE**  
Features low-oil shutdown

**PROFESSIONAL-GRADE TRIPLEX PUMP**  
Ceramic-coated pistons mean long life

## BELT DRIVE

Powerful. Compact. Long-lasting. These professional-grade power washers feature heavy-duty belt drives for longer pump life than direct drive models. You can also count on a compact, lightweight design for easy mobility around the jobsite.



### STEEL-REINFORCED HOSE

Quick-change connectors make hose connections a snap

### PROFESSIONAL-GRADE ERGONOMIC SPRAY GUN

Cushion grip handle and easy-to-pull trigger reduce fatigue and improve comfort

### HEAVY DUTY BELT DRIVE AR TRIPLEX PUMP

Up to 3X longer life than direct drive triplex pumps

### OVERSIZED PNEUMATIC WHEELS

Easily handle rugged jobsite terrain

### COMPACT, LIGHTWEIGHT DESIGN

Up to 50 lbs. less weight than other belt-drive power washers

### POWERFUL GENERAC OHV HORIZONTAL-SHAFT ENGINE

Features low-oil shutdown



# 3100-4200 PSI

PROFESSIONAL  
POWER WASHERS



## SPECIFICATIONS

DIRECT DRIVE	3100 PSI	3600 PSI	3800 PSI	4200 PSI
Model Number (49-State/CARB)	6590 / 6607	6855	6564	6565
GPM	2.8	2.6	3.6	4
Cleaning Power (PSI x GPM)	8680	9360	13680	16800
Engine	212cc Generac OHV w/ low oil shutdown	212cc Generac OHV w/ low oil shutdown	302cc Generac OHV w/ low oil shutdown	420cc Generac OHV w/ low oil shutdown
Pump	Triplex with ceramic-coated pistons & pressure adjustment valve	Triplex with ceramic-coated pistons & pressure adjustment valve	Triplex with ceramic-coated pistons & pressure adjustment valve	Triplex with ceramic-coated pistons & pressure adjustment valve
Spray Gun Type	Professional-grade w/ adjustable side handle	Professional-grade w/ adjustable side handle	Professional-grade w/ adjustable side handle	Professional-grade w/ adjustable side handle
Hose Type	5/16" x 35' steel reinforced	5/16" x 35' steel reinforced	3/8" x 35' steel reinforced	3/8" x 35' steel reinforced
Soap Tanks	Siphon hose	Siphon hose	Siphon hose	Siphon hose
Quick-Connect Nozzle Tips	(5) 0°, 15°, 25°, 40°, soap	(5) 0°, 15°, 25°, 40°, soap	(5) 0°, 15°, 25°, 40°, soap	(5) 0°, 15°, 25°, 40°, soap
Wheel Type	10" never-flat	10" never-flat	10" never-flat	12" pneumatic
Dimensions (L" x W" x H")	31.8 x 24.3 x 38	31.8 x 24.3 x 38	34.5 x 26.8 x 42.5	34.5 x 28.3 x 42.5
Product Weight	102.5 lbs	102.5 lbs	129 lbs	146.5 lbs
Warranty	3 year limited	3 year limited	3 year limited	3 year limited

BELT DRIVE	3800 PSI
Model Number (49-State/CARB)	6712
GPM	3.2
Cleaning Power (PSI x GPM)	12160
Engine	302cc Generac OHV w/ low-oil shutdown
Pump Type	Triplex with ceramic-coated pistons & pressure adjustment valve
Spray Gun Type	Professional-grade w/ adjustable side handle
Hose Type	5/16" x 35' steel reinforced
Quick-Connect Nozzle Tips	(5) 0°, 15°, 25°, 40°, soap
Wheel Type	10" pneumatic
Dimensions (L" x W" x H")	35.5 x 25.25 x 26.75
Product Weight	134 lbs
Warranty	3 year limited

All portable specifications and models subject to change. Please consult factory for availability.

# GENERAC®

0L2784 REV. A 05/2015

©2015 Generac Power Systems, Inc. All Rights Reserved.  
Specifications are subject to change without notice.

Generac Power Systems, Inc.  
S45 W29290 Hwy. 59, Waukesha, WI 53189  
1-888-GENERAC (1-888-436-3722)

generac.com